

FEATURES

- 1/30,000 Display Resolution
- Suitable for Laboratory and Jewellery Applications
- 13 User-Programmable Weight Units: Metric, Metric Carat, Pound (Avoirdupois), Dram (Avoirdupois), Grain (UK), Troy Ounce, Pennyweight, Momme (Japan), Tael (Taiwan), Tael (China), Troy Tael, Tola (India)
- Equipped with: Power On Zero-Tracking, Manual Zero Setting, Power Saving, Auto Calibration, Percentage and Counting Function
- Long Battery Operating Time: 100+ Hours
- Dual Power: 4 x C-Size Batteries or Power Adaptor
- Low Battery Warning Signal
- 6 x 13mm Bold-Digit, Wide-Angle Display Digits
- Power Adaptor, Backlight, Adjustable Feet and Dust Cover Included
- NJW-300 and NJW-600 Equipped with Level Bubble and Wind Break



NJW-300

OPTIONS

- RS-232 Interface Output

SPECIFICATIONS

MODEL	NJW-300	NJW-600	NJW-1500	NJW-3000
Capacity	300g	600g	1,500g	3,000g
Division	0.01g	0.02g	0.05g	0.1g
Platter Size	Ø110mm		140mm x 170mm	
Power Source	4 x C-Size Batteries or Power Adaptor			
Environment	0°C to 40°C, Non-Condensed, Relative Humidity ≤ 85%			
Boxed Size	NJW-300 and NJW-600: 310mmL x 300mmW x 170mmH Other Models: 360mmL x 275mmW x 100mmH			
Net/Gross Weight	NJW-300 and NJW-600: 1.22kg Net, 2.00kg Gross Other Models: 1.24kg Net, 1.60kg Gross			

DIMENSIONS

