

FEATURES

- All Stainless Steel Housing
- Wash Down Design, IP-65 Environmental Rating
- Sealed Electronics
- Low Profile, Compact Size, Heavy Duty
- Dual (Metric and Imperial) Weighing Units
- Dual Power: Internal Rechargeable Battery or External Power Adaptor
- Accumulation Function
- Power On Zero-Tracking
- Re-Zero Function
- Full Subtractive Tare
- Power Saving
- Low Battery Warning Indication
- Auto Calibration Function
- 6 x 19mm Wide-Angle LCD Display Digits
- All Stainless Steel Adjustable Feet, Built-In Rechargeable Battery, Dust Cover and External Power Adaptor Included



GS-3000

DIMENSIONS



OPTIONS

- Level Bubble
- EL Backlighting

SPECIFICATIONS

MODEL	GS-1200	GS-1500	GS-3000	GS-6000	GS-12K	GS-15K
Capacity	1,200g	1,500g	3,000g	6,000g	12kg	15kg
1/3,000 Division	-	0.5g	1g	2g	-	0.005kg
1/6,000 Division	0.2g	-	0.05g	1g	0.002kg	-
Platter Size	210mm x 210mm					
Environment	0°C to 40°C, Non-Condensed, Relative Humidity ≤ 85%					
Standard Package	4 x Units per Shipping Carton 720mmW x 415mmL x 380mmH, 13.6kg Net, 19kg Gross					

Colonial Weighing Australia Pty Ltd

Unit 11/47-51 Little Boundary Road, Laverton North, Victoria, 3026, Australia

Telephone: (03) 9315 2088
Facsimile: (03) 9315 2494

www.colonialweighing.com.au
sales@colonialweighing.com.au

Established 1930
ISO 9001 Endorsed